



TMAX 400



3 - 4,6 m
10' - 15'

1.3 Kg
2,87 lb

1 m
3,3'

V peak	113	mm	1.0 - 1.6 mm .040" - 1/16"	X	450A CO ₂ 400A Mix
--------	-----	----	-------------------------------	---	----------------------------------



CODE	↔	⚡
MA6385	3 m / 10'	EURO - TW
MA6386	4 m / 12'	EURO - TW
MA6387	4,6 m / 15'	EURO - TW
MA6394T	3 m / 10'	TWECO®
MA6395T	4 m / 12'	TWECO®
MA6396T	4,6 m / 15'	TWECO®
MA6394M	3 m / 10'	MILLER®
MA6395M	4 m / 12'	MILLER®
MA6396M	4,6 m / 15'	MILLER®
MA6394L	3 m / 10'	LINCOLN®
MA6395L	4 m / 12'	LINCOLN®
MA6396L	4,6 m / 15'	LINCOLN®

CODE	↔	⚡	+	CODE	KIT
MA6394	3 m / 10'	5/8-18 UNF	+	AR0170	Tweco® 1/4 KIT
MA6395	4 m / 12'	5/8-18 UNF		AR0172	Lincoln® KIT
MA6396	4,6 m / 15'	5/8-18 UNF		AR0173	Miller® KIT

Liner included





Kit to be assembled by a qualified technician
[see page 291](#)





Ø mm	Ø in	Cu for Al	CuCrZr
0,8	.030		MD0250-78
0,9	.035		MD0250-79
1,0	.040		MD0250-80
1,2	.045	MD0250-62	MD0250-82
1,4	.052	MD0250-64	MD0250-84
1,6	1/16	MD0250-66	MD0250-86
2,0	5/64		MD0250-90
2,4	3/32		MD0250-94

MC0298	MC0011	MC0012	MC0013
--------	--------	---------------	--------



STANDARD

(REF.)

